


ASSM-114B-4C-D43M is an assembly of 4x Stacked version of Low-PIM 4-Way In-Line Reactive Power Splitter with 6' 3/8" Jumper Cables connected to split ends of the splitters. These are ideal for 4x4 MIMO Applications. The splitters are designed to evenly split high power signals between 600MHz and 6000MHz. The outputs of the splitters are connected to Innowave RF 6' weather-proof 3/8" Jumper Cables (JW375 Series) with 4.3-10 Male connectors. These assemblies are rated to be used in extreme weather and environmental conditions and are perfect for Pole-Mount applications. Other stacked options are also available on request.


FEATURES:

- 4x Stacked for 4x4 MIMO Applications w/ Jumpers on the split ends
- Compact, Small Form Factor design
- Wide bandwidth 600 MHz – 6000 MHz
- Easy Pole-Mounting Options just before the Antenna
- **LTE-LAA, CBRS and C-Band** Ready
- **In-Line** Reactive Splitter
- 6' 3/8" Weather-Proof Jumpers connected to the outputs of the splitter
- Superior Construction and High Power Handling
- Low Insertion Loss and low VSWR
- Low PIM, -161dBc
- In Stock to low lead time delivery
- Weatherproof / Outdoor unit




SPECIFICATIONS:

Frequency Range:	600 MHz – 6000 MHz	Impedance:	50Ω
Insertion Loss(Splitter Only):	0.35 dB @ 600-2700 MHz 0.50 dB @ 2700-4200 MHz 0.60 dB @ 4200-6000 MHz (Over the theoretical loss of 6 dB)	Temperature Range:	-30°C to 75°C
VSWR:	≤ 1.30 @ 600-2700 MHz ≤ 1.35 @ 2700-4200 MHz ≤ 1.35 @ 4200-6000 MHz	Weight:	42 lbs (w/ 12x 6' cables)
Power Handling:	300 W (Avg)	Housing Finish:	Aluminum Body
PIM – 3 rd :	-161 dBc (2 Tones +43 dBm)	Mounting Method:	Mounting Holes
		Humidity:	5% - 95%
		Environment:	IP67



Dimensions for ASSM-114B-4C-D43M



Please contact our sales department at 737-200-7090 or sales@InnowaveRF.com for any custom requirements.

© Innowave RF, LLC. All Rights Reserved. Specs can change without notice. Drawings are for reference purpose only.