



FEATURES:

- Splits or combines the **Low-Band & Mid-Band** (617MHz-2360MHz), **BRS Band** (2496MHz-2690MHz), **CBRS Band** (3550MHz-3700MHz), **DoD & C-Band** (3450MHz-3530MHz, 3720MHz-4200MHz)
- Stacked / Dual unit for MIMO applications
- Minimum 40dB Isolation between the bands
- Very low Insertion Loss with superior out of band rejections
- Available in 4.3-10 or NEX10 Connectors
- Ease of Mounting with mounting holes and brackets
- Low-PIM with High Power Handling
- RoHS Compliant
- Weatherproof for Outdoor installation
- In Stock and Available Immediately



ELECTRICAL SPECIFICATIONS:

Frequency Bands	600(B71)/700+FN 850/PCS/AWS/WCS 617MHz - 2360MHz	BRS 2496MHz - 2690MHz	CBRS 3550MHz - 3700MHz	DoD/C-Band 3450MHz - 3530MHz 3720MHz - 4200MHz
Passband Insertion Loss	0.30 dB			
Isolation	≥ 40 dB			
Return Loss	21dB			
Impedance	50 Ohms			
Input Power / Port	150 Watts (Avg)			
DC Pass Current	4000 mA (Typ) (DC Block Available on Request)			
Intermodulation (PIM-3 rd)*	-161dBc (2 Tones +43 dBm)			
Lightning Protection	8/20S 10KA Pulse (IEC801-5)			
MTBF Hours	≥ 500,000			

MECHANICAL & ENVIRONMENTAL SPECIFICATIONS:

Connectors:	4.3-10 (D43) / NEX10 (X10)
Housing Finish:	Aluminum Body
Mounting Method:	Mounting Bracket
Weight:	13.00 lbs
Temperature Range:	-30°C to 75°C
Humidity:	5% – 95%
Environment:	IP67


ORDERING INFO:

Stacked Model:

4.3-10 Connector:	Part#: 942C-2050-3700-D43
NEX10 Connector:	Part#: 942C-2050-3700-X10

SINGLE MODEL AVAILABLE

Dimensions for 942C-2050-3700-D43



Please contact our sales department at 737-200-7090 or sales@innowaveRF.com for any custom requirements.
 © Innwave RF, LLC. All Rights Reserved. Specs can change without notice. Drawings are for reference purpose only.