


FEATURES:

- Splits or combines the **600 (B71), 700+FN, 850 Bands** (617MHz-896MHz), **PCS Band** (1850MHz-2000MHz) and **AWS-1, AWS-3, WCS Bands** (1695MHz-1780MHz, 2110MHz-2360MHz)
- Available in **Dual / Stacked Model (932C Series)**
- Minimum 40dB Isolation between the bands
- Very low Insertion Loss with superior out of band rejections
- Available in 4.3-10 or NEX10 Connectors
- Ease of Mounting with mounting holes and brackets
- Low-PIM with High Power Handling
- RoHS Compliant
- Weatherproof for Outdoor installation
- In Stock and Available Immediately



ELECTRICAL SPECIFICATIONS:

Frequency Bands	600, 700+FN, 850 617MHz - 896MHz	PCS 1850MHz - 2000MHz	AWS-1, AWS-3, WCS 1695MHz - 1780MHz 2110MHz - 2360MHz
Passband Insertion Loss	0.25 dB (Typ)		
Isolation	≥ 40 dB		
Return Loss	21 dB (Typ)		
Impedance	50 Ohms		
Input Power / Port	150 Watts (Avg)		
DC Pass Current	4000 mA (Typ) (DC Block Available on Request)		
Intermodulation (PIM - 3 rd)	-161dBc (Min) (2 Tones +43 dBm)		
Lightning Protection	8/20S 10kA Pulse (IEC801-5)		
MTBF Hours	≥ 500,000		

MECHANICAL SPECIFICATIONS:

Connectors:	4.3-10 (D43) / NEX10 (X10)
Housing Finish:	Aluminum Body
Mounting Method:	Mounting Bracket
Temperature Range:	-30°C to 75°C
Humidity:	5% – 95%
Weight:	4.00 lbs
Environment:	IP67


ORDERING INFO:

Single Model:

4.3-10 Connector:	Part#: 931C-1444-2390-D43
NEX10 Connector:	Part#: 931C-1444-2390-X10

STACKED MODEL AVAILABLE

Dimensions for 931C-1444-2390-D43



DUAL/STACKED UNITS AVAILABLE (932C SERIES)

Please contact our sales department at 737-200-7090 or sales@InnowaveRF.com for any custom requirements.

© Innowave RF, LLC. All Rights Reserved. Specs can change without notice. Drawings are for reference purpose only.